



US009409210B2

(12) **United States Patent**  
**Berkhout et al.**

(10) **Patent No.:** **US 9,409,210 B2**  
(45) **Date of Patent:** **\*Aug. 9, 2016**

(54) **SEPARATION-APPARATUS**

(75) Inventors: **Simon Peter Maria Berkhout**, Delft (NL); **Peter Carlo Rem**, Rijswijk (NL)

(73) Assignee: **ADR TECHNOLOGY B.V.**, Rotterdam (NL)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 607 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/936,058**

(22) PCT Filed: **Apr. 1, 2009**

(86) PCT No.: **PCT/NL2009/050165**

§ 371 (c)(1),

(2), (4) Date: **Dec. 10, 2010**

(87) PCT Pub. No.: **WO2009/123452**

PCT Pub. Date: **Oct. 8, 2009**

(65) **Prior Publication Data**

US 2011/0084005 A1 Apr. 14, 2011

(30) **Foreign Application Priority Data**

Apr. 2, 2008 (NL) ..... 2001431

(51) **Int. Cl.**

**B07C 5/00** (2006.01)

**B07B 13/10** (2006.01)

(52) **U.S. Cl.**

CPC ..... **B07B 13/10** (2013.01)

(58) **Field of Classification Search**

CPC ..... B07B 13/00; B07B 13/10; B07B 13/003; B22C 5/06

USPC ..... 209/637, 638, 640, 642, 44.2, 639, 644

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,095,385 A \* 10/1937 Heisserman ..... B22C 5/02 209/145

2,662,641 A 12/1953 Clark

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1895796 A 1/2007

CN 201482560 U 5/2010

(Continued)

OTHER PUBLICATIONS

International Preliminary Report on Patentability dated Aug. 23, 2010 from PCT/NL2009/050165.

(Continued)

*Primary Examiner* — Joseph C Rodriguez

*Assistant Examiner* — Kalyanavenkateshware Kumar

(74) *Attorney, Agent, or Firm* — Swanson & Bratschun, L.L.C.

(57) **ABSTRACT**

The invention relates to a separation-apparatus for separating from a particle-stream at least a first fraction with particles of a first group of dimensions, and a second fraction with particles of a second group of dimensions, comprising an infeed-device for the particle-stream, a rotatable drum having at its circumference plates, each plate having a radially extending hitting surface for the particles, at least a first receiving area proximal to the drum for receipt therein of particles of the first fraction, and at least a second receiving area distant from the drum for receipt therein of particles of the second fraction, wherein the apparatus has a housing so as to protect the particles from outside weather-conditions, allowing that the particles of the particle-stream to be processed by said apparatus have dimensions in the range 0-15 mm.

**14 Claims, 3 Drawing Sheets**

